

## Flange Table - Nominated Size: 50mm (2")

| Flange Std | Table       | Flg Dia    | Thickness - Min                       |       |    | Drilling |           |           |           |
|------------|-------------|------------|---------------------------------------|-------|----|----------|-----------|-----------|-----------|
|            |             |            | C.I.                                  | Steel | GM | PCD      | No. Holes | DIA Holes | Dia Bolts |
| AS2129     | <b>C</b>    | <b>150</b> | 19                                    | 8     | 19 | 114      | 4         | 18        | M16       |
|            | <b>D</b>    | <b>150</b> | 17                                    | 14    | 10 | 114      | 4         | 18        | M16       |
|            | <b>E</b>    | <b>150</b> | 19                                    | 14    | 10 | 114      | 4         | 18        | M16       |
|            | <b>F</b>    | <b>165</b> | 19                                    | 16    | 11 | 127      | 4         | 18        | M16       |
|            | <b>H</b>    | <b>165</b> | 25                                    | 19    | 13 | 127      | 4         | 18        | M16       |
|            | <b>J</b>    | <b>165</b> | -                                     | 25    | 25 | 127      | 4         | 22        | M20       |
| BS4504     | <b>16</b>   | <b>165</b> | 20                                    | -     | 11 | 125      | 4         | 18        | M16       |
|            | <b>25</b>   | <b>165</b> | 22                                    | -     | 11 | 125      | 4         | 18        | M16       |
|            | <b>40</b>   | <b>165</b> | -                                     | 20    | 13 | 125      | 4         | 18        | M16       |
| ANSI       | <b>150</b>  | <b>152</b> | 16                                    | 19    | -  | 121      | 4         | 19        | 5/8"      |
|            | <b>300</b>  | <b>165</b> | 22                                    | 22    | -  | 127      | 8         | 19        | 5/8"      |
|            | <b>600</b>  | <b>165</b> | -                                     | 25    | -  | 127      | 8         | 19        | 5/8"      |
|            | <b>900</b>  |            | <b>USE CLASS 1500 FLANGE DRILLING</b> |       |    |          |           |           |           |
|            | <b>1500</b> | <b>216</b> | -                                     | 38    | -  | 165      | 8         | 25        | 7/8"      |
|            | <b>2500</b> | <b>235</b> | -                                     | 51    | -  | 172      | 8         | 29        | 1"        |